


# Construction Resources



## TIERRAFINO TECHNICAL SHEET T2

---

### TIERRAFINO CONTACT

- Uses** *Tierrafino Contact* serves as a primer for *Tierrafino Clay Plaster* to enable maximum adhesion. It can be used as both a primer for smooth surfaces such as plasterboard, concrete, paint etc and as a strengthener for old or other plastered surfaces to achieve an impact-resistant, dust-free and rough textured surface.
- Properties** *Tierrafino Contact* is almost white when completely dry. It helps to provide a breathing and humidity regulating finish.
- Containers** Supplied in 5 litre and 10 litre containers.
- Coverage** Approximately 6 m<sup>2</sup> per litre, depending on the absorbency of the surface.
- Preparation** Apply *Tierrafino Contact* to a grease and dust free surface. Do not add more than 20% water to *Tierrafino Contact*.
- Application** Apply *Tierrafino Contact* undiluted by rolling or brushing. Clean tools directly after use with warm soapy water.
- Used with** *Tierrafino Clay Plaster*
- Drying times** *Tierrafino Contact* is dry after six hours depending on temperature, humidity and absorbency of the surface.
- Storage:** Keep well sealed in a dry and cool place, free from frost. Keep out of the reach of children.
- Ingredients** Cellulose, methyl cellulose, calcium carbonate, citric acid, acetic acid, chalk, marble powder, marble sand, china clay, water and 0.1% synthetic preservative.
- Safety** *Tierrafino Contact* is not flammable.
- Risk class** None (non-inflammable)

This technical information sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements. This sheet was issued on 19 May 2006 and may be superseded by later editions.